



## 8.7/15 kV XLPE insulated, radial and longitudinally sealed, single core cables with copper conductor



Code: N2XS(FL)2Y, CU/XLPE/LW/CWS/LW/PE

Standards: IEC 60502 - 2, VDE 0276 - 620

### Technical Data

Max. operating temperature : 90 °C  
 Max. short circuit temperature : 250 °C (max. 5 sec.)  
 Rated voltage : 8.7/15 kV  
 Min. bending radius : 15 x D  
 D : Cable outer diameter

### Application

These are cables with low dielectric losses used in energy networks with sudden load changes. Laid in residential or industrial areas, underground or in ducts. If the cable gets water inside due to the mechanical damages, swellable tapes prevent the movement of the water inside the cable.

### Construction

- 1 Stranded copper conductors
- 2 Inner semi conductive layer
- 3 XLPE insulation
- 4 Outer semi conductive layer
- 5 Semi conductive swelling tape
- 6 Copper screen
- 7 Swellable tape
- 8 PE coated aluminium foil.
- 9 PE outer jacket.

DIMENSION AND WEIGHTS			ELECTRICAL PROPERTIES									
Nominal Cross Section	Overall Diameter (approx)	Net Weight (approx)	Delivery Length	DC Conductor Resistance at 20 °C Max	DC Conductor Resistance at 90 °C Max	Operation Inductance		Operation Capacitance	Current Carrying Capacity (A)			
mm <sup>2</sup>	mm	kg/km	m	ohm/km	ohm/km	*** mH/km	** mH/km	µF/km	In ground at 20 °C		In air at 30 °C	
									***	**	***	**
1x35/16	28,0	900	1000	0,524	0,6707	0,674	0,429	0,181	212	187	231	195
1x50/16	29,0	1100	1000	0,387	0,4954	0,648	0,410	0,201	249	220	277	234
1x70/16	30,0	1300	1000	0,268	0,3430	0,617	0,387	0,229	303	269	345	292
1x95/16	32,0	1600	1000	0,193	0,2470	0,593	0,371	0,255	358	321	418	354
1x120/16	34,0	1850	1000	0,153	0,1958	0,574	0,358	0,278	404	364	481	407
1x150/25	36,0	2250	1000	0,124	0,1587	0,557	0,348	0,302	441	405	537	460
1x185/25	37,0	2600	1000	0,0991	0,1268	0,541	0,337	0,328	493	457	612	527
1x240/25	40,0	3200	1000	0,0754	0,0965	0,521	0,326	0,363	563	528	716	621
1x300/25	42,0	3800	1000	0,0601	0,0769	0,504	0,316	0,398	626	593	811	709
1x400/35	46,0	4900	1000	0,0470	0,0602	0,483	0,305	0,447	676	665	901	815
1x500/35	48,0	5900	500	0,0366	0,0468	0,467	0,297	0,491	743	739	1006	921
1x630/35	54,0	7150	500	0,0283	0,0362	0,451	0,289	0,543	820	818	1130	1045

Note  
 In ground : Current carrying capacities are valid under the following conditions;  
 : 20 °C, 70 cm depth of lay, soil-thermal resistivity 1 K.m/W, load factor 0.7  
 In air : 30 °C, load factor 1.0  
 \*\*\* : Flat formation, clearance between cables; in air = 1 x Cable outer diameter, in ground = 7 cm  
 \*\* : Trefoil formation  
 Number of system : 1