



Code: LIYY **Standard:** TS 13755, VDE 0812, TSE K 353

L : Bundle wire
Y : PVC

LIYY-OB : Cables without number, with different colored cores

LIYY-JB : Cables without number, with different colored cores and cables with ground core (Yellow / Green)

LIYY-OZ : White numbered core cables on insulated black

LIYY-JZ : White numbered core cables on insulated black and cables with ground core (Yellow / Green)

Technical Properties

Operating Temperature : -5 °C / + 70 °C
 Storage Temperature : -30 °C / + 70 °C
 Min. bending radius (fixed) : 7,5 x D
 Min. bending radius (moved) : 15 x D

Fire Performance Tests

Vertical Flame Spread / EN 60332-1-2, IEC 60332-1-2,
 DIN EN 60332-1-2 (VDE 0482-332-1-2)

Construction

- 1- Flexible copper conductor / Class 5 (EN 60228, IEC 60228, DIN VDE 0295)
- 2- PVC insulation (EN 50290-2-21)
- 3- Single twist in layers
- 4- Separator tape
- 5- PVC Sheath (EN 50290-2-22)

Electrical Properties

Cross-Section (mm ²)	Current Carrying Capacity (A)
0,5	6
0,75	13
1	16
1,5	20
2,5	25

Applications

Appropriate for use in narrow space implementations thanks to its flexible structure, these cables can be used in instrument and control engineering, industrial electronics, computer and office engineering, indoor communication, audio and security systems.

Number of Cores and Cross-Section	Outer Diameter (Approx)	Copper Weight (Approx)	Cable Weight (Approx)	Conductor Resistance (max.)	Operating Voltage	Delivery Length
mm ²	mm	kg/km	kg/km	Ω/km	(V)	m
2x0,50	4,6	9,0	25	38,9	500	100 / 500 / 1000
3x0,50	4,9	13,5	33	38,9	500	100 / 500 / 1000
4x0,50	5,4	18,0	41	38,9	500	100 / 500 / 1000
5x0,50	5,8	22,5	51	38,9	500	100 / 500 / 1000
6x0,50	6,4	27,0	60	38,9	500	100 / 500 / 1000
7x0,50	6,4	31,5	65	38,9	500	100 / 500 / 1000
8x0,50	7,1	36,0	80	38,9	500	100 / 500 / 1000
10x0,50	8,1	45,0	96	38,9	500	100 / 500 / 1000
12x0,50	8,4	53,9	106	38,9	500	100 / 500 / 1000
2x0,75	5,0	13,5	31	26,0	500	100 / 500 / 1000
3x0,75	5,3	20,2	42	26,0	500	100 / 500 / 1000
4x0,75	5,7	27,0	52	26,0	500	100 / 500 / 1000
5x0,75	6,3	33,7	65	26,0	500	100 / 500 / 1000
6x0,75	6,8	40,5	77	26,0	500	100 / 500 / 1000
7x0,75	6,8	47,2	84	26,0	500	100 / 500 / 1000
8x0,75	7,7	53,9	103	26,0	500	100 / 500 / 1000
10x0,75	8,7	67,4	124	26,0	500	100 / 500 / 1000
12x0,75	9,0	80,9	138	26,0	500	100 / 500 / 1000

Number of Cores and Cross-Section	Outer Diameter (Approx)	Copper Weight (Approx)	Cable Weight (Approx)	Conductor Resistance (max.)	Operating Voltage	Delivery Length
mm ²	mm	kg/km	kg/km	Ω/km	(V)	m
2x1,0	5,4	18,0	38	19,5	500	100 / 500 / 1000
3x1,0	5,7	27,0	51	19,5	500	100 / 500 / 1000
4x1,0	6,3	36,0	65	19,5	500	100 / 500 / 1000
5x1,0	6,9	45,0	80	19,5	500	100 / 500 / 1000
6x1,0	7,5	53,9	96	19,5	500	100 / 500 / 1000
7x1,0	7,5	62,9	105	19,5	500	100 / 500 / 1000
8x1,0	8,4	71,9	129	19,5	500	100 / 500 / 1000
10x1,0	9,6	89,9	155	19,5	500	100 / 500 / 1000
12x1,0	9,9	107,9	173	19,5	900	100 / 500 / 1000
2x1,5	6,4	26,3	52	13,3	900	100 / 500 / 1000
3x1,5	6,8	39,5	72	13,3	900	100 / 500 / 1000
4x1,5	7,5	52,7	92	13,3	900	100 / 500 / 1000
5x1,5	8,2	65,9	114	13,3	900	100 / 500 / 1000
6x1,5	9,0	79,0	137	13,3	900	100 / 500 / 1000
7x1,5	9,0	92,2	150	13,3	900	100 / 500 / 1000
8x1,5	10,1	105,4	186	13,3	900	100 / 500 / 1000
10x1,5	11,8	131,7	229	13,3	900	100 / 500 / 1000
12x1,5	12,2	158,0	255	13,3	900	100 / 500 / 1000
2x2,5	7,1	40,4	70	7,98	900	100 / 500 / 1000
3x2,5	7,6	60,6	97	7,98	900	100 / 500 / 1000
4x2,5	8,3	80,8	125	7,98	900	100 / 500 / 1000
5x2,5	9,2	101,0	157	7,98	900	100 / 500 / 1000
6x2,5	10,1	121,2	189	7,98	900	100 / 500 / 1000
7x2,5	10,1	141,4	208	7,98	900	100 / 500 / 1000
8x2,5	11,6	161,6	262	7,98	900	100 / 500 / 1000
10x2,5	13,2	201,9	316	7,98	900	100 / 500 / 1000
12x2,5	13,7	242,3	355	7,98	900	100 / 500 / 1000